


Porca Travante Baixa

com Nylon

Aço Baixo Carbono - Grau 2 / Classe 8



Acabamento - Zincado Branco

Dimensões - DIN 985

Rosca - ANSI B 1.1 / DIN 13



Porca Travante Baixa c/ Nylon

Diâmetro (d)	Passo (p)	Altura (m)	Chave (s)	Código
#10	BSW-24	0,187	3/8	02594 ²⁰⁰⁰
1/4	UNC-20	0,256	7/16	02595 ¹⁰⁰⁰
5/16	UNC-18	0,359	1/2	02596 ⁵⁰⁰
3/8	UNC-16	0,375	9/16	02597 ⁵⁰⁰
7/16	UNC-14	0,437	11/16	02598 ⁵⁰⁰
1/2	UNC-13	0,500	3/4	02599 ²⁰⁰
1/2	BSW-12	0,500	3/4	02600 ²⁰⁰
9/16	UNC-12	0,562	7/8	02601 ²⁰⁰
5/8	UNC-11	0,625	15/16	02602 ¹⁰⁰
3/4	UNC-10	0,700	1-1/8	02603 ¹⁰⁰
7/8	UNC-9	0,764	1-5/16	02604 ⁵⁰
1	UNC-8	0,842	1-1/2	02605 ⁵⁰

Porca Travante Baixa c/ Nylon DIN 985

Diâmetro (d)	Passo (p)	Altura (m)	Chave (s)	Código
M3	MA-0,50	4	5,5	02606 ⁵⁰⁰⁰
M4	MA-0,70	5	7	02607 ²⁰⁰⁰
M5	MA-0,80	5	8	02608 ²⁰⁰⁰
M6	MA-1,00	6	10	02609 ¹⁰⁰⁰
M8	MA-1,25	8	13	02610 ⁵⁰⁰
M10	MA-1,50	10	17	02611 ⁵⁰⁰
M12	MA-1,75	12	19	02612 ²⁰⁰
M14	MA-2,00	14	22	02613 ²⁰⁰
M16	MA-2,00	16	24	02614 ¹⁰⁰
M18	MA-2,50	18	27	02615 ¹⁰⁰
M20	MA-2,50	20	30	02616 ¹⁰⁰
M22	MA-2,50	22	32	02617 ⁵⁰
M24	MA-3,00	24	36	02618 ⁵⁰